



BI7600 Strut Spring Compressor

- 3,000 LB Max Compression Capacity
- 3.5" Min/11.5" Max Spring Diameters
- Does Not Require Adaptors • Mounting Options
- HD Acme Thread • Multi-Position Hooks
- All-Steel Construction *MADE IN USA*

USER \$1,419.00 SRP **\$1,324.40**

BIG300A Pressure Brake Bleeder

- Large 4-Gallon Reservoir • 1-Person Operation
- Continually Regulated Pressure up to 60 PSI
- Quick Couple with No Air Introduced
- High Grade Ball Valves

USER \$497.00 SRP **\$463.86**



FOB



FOB

BI5045 Tire Spreader

- Maximum Bead Diameter: 20"
- Maximum Tire X-Section: 13.5"
- Spread Arm Type: Gas Spring Assist
- Spread Arm Operation: Hand • Compact Footprint
- Working Height: 36.25" • LED Light • Roller
- Sawtooth Hook Adjustment • All Steel Construction
- MADE IN USA*

SRP **\$812.00**

LTD QTY



BI2130 Tire Inflation Cage

- 3 Bars 34" Max Tire Diameter
- 2 1/4" High Yield Strength Steel Tubing
- Arched Bar Design • 21.5" Max Tire Width
- 120 PSI Max Inflation Pressure
- MADE IN USA*

SRP **\$481.00**

LTD QTY



JIM1087-2 Hose Repair Kit, 1/4" - 5/16"

- Hose Barbed End is 5/16"; Threaded End is 12MM
- Can be used with either .250" or .3125" Hose
- Works well to Repair **JIM1087** Leakdown Tester, or 12MM Spark Plug Threads Found on all Twin Cams, or XL 1986 & later as well as Screamin' Eagle EVO BT Heads

USER \$59.80 SRP **\$51.58**



JIM753 Mighty Bite Flywheel Lock

- Use on ALL Twin Cam Motors
- To Lock Crankshaft when Servicing
- Just Take Out the Crank Position Sensor & Install "Mighty Bite" into Case
- Tool has an Added O-Ring to Prevent Oil Seepage


USER \$51.65 SRP **\$45.61**



JIM33071-73 Wheel Bearing Race Remover & Installer Tool

- Use on Big Twin & Sportster® 1973-99; Use on Buell® 1987-99
- Use to Remove & Install Bearing Cups in Cast Wheels
- Use with JIMS® Handle **JIM33416-80**, Below and Brass Hammer, **JIM1080**
- Comes with 1 Spacer, **JIM2388**

USER \$162.10 SRP **\$140.18**



JIM1772 7-IN-1 Torx® Key Set

- Keys are Heat Treated Alloy Steel
- Folded Length is 4 1/4"
- **Includes Sizes:** T-10, T-15, T-20, T-25, T-27, T-30 & T-40

USER \$65.10 SRP **\$50.44**

JIM38515-91 Nut for Clutch Spring Compressor Tool

- Use on ALL Sportster® 1991 - Present
- Use on ALL Buell® 1991 - 2009
- Includes ALL Buell® Blast, except 1125R
- Must be used with **JIM38515-90** Main Body
- **Includes:** Nut, Washer, Retaining Ring & Instruction Sheet

USER \$76.20 SRP **\$66.14**



JIM970 3rd Hand Axle Locker Tool

- Use on all 2002 and later FL
- Have you Noticed as you are Torquing Down the Axle Nut after you set the Proper Belt Tension, (Deflection) the Welded Axle Nut will move to the Low Side of Adjuster Cam? This Movement will allow the Belt to lose Adjustment. Place this Tool over the Welded Nut on Left Side with the Neck Portion of the Tool Resting over the Swing Arm.

USER \$85.65 SRP **\$78.16**

